



CONVENIENT

Easy Installation







The Grundfos SCALA1 is an all-in-one, self-priming pump with built-in Bluetooth® connectivity, making it simple to install, customise, control and troubleshoot using the Grundfos GO App.


TECHNICAL & PERFORMANCE DATA

PHYSICAL ATTRIBUTES





PERFORMANCE CURVE



Model	Motor Power P2 (kW)	Connections		Dimensions (mm)					Weight
		Inlet	Outlet	A (I)	B (w)	C (h)	D (inlet)	E (outlet)	(kg)
SCALA1 3-45	0.80	1" Male	1" Male	466	202	316	171	263	12
SCALA1 5-55	1.00	1" Male	1" Male	466	202	316	171	263	14

OPERATING CONDITIONS

Ambient Temperature	0°C to +55°C				
Liquid Temperature	0°C to +45°C				
System Pressure	Max. 8 bar				
Sound Pressure	Max. 55 dB				

TECHNICAL DATA

Power Supply Voltage	230 Volt, 50 Hz				
Power Supply Cable	1.5 m with plug				
Enclosure Class	Suitable for outdoor installation (IPX4D)				

TWIN BOOSTER OPTION

Where higher flow is required SCALA1 can be set up as a Twin Booster in either Duty Assist or Duty Standby modes.

Twin Booster Kit includes:

Manifolds, isolation valves, base plate, communication cable and fixing screws.



TAKE CONTROL & GET PUMPINGUSING THE GRUNDFOS **GO** APP





Using the Grundfos GO App customers can access advanced features of SCALA1 and further customise and control the pump's functions.



